

CLAIM AMENDMENTS

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently amended) A medical device, comprising:
an imaging element for subcutaneous placement in a tissue mass to identify an area of interest in the tissue mass; and
a guide element ~~connected to the imaging element and having a separable portion;~~
wherein ~~when the guide element is connected with the imaging element, such that after~~
the imaging element is placed has been deployed within the tissue mass[,] and a delivery apparatus used to deploy the imaging element has been removed from the tissue mass, (i) the imaging element is connected to the guide element and at least part of the guide element extends exteriorly of the tissue mass to permit the locating of the area of interest, and (ii) after placement when the separable portion is adapted to be separated from the guide element removed from the tissue mass, such that no part of the guide element extends exteriorly of the tissue mass.

2. (Original) The medical device according to claim 1, wherein the separable portion comprises the entire guide element.

3. (Original) The medical device according to claim 1, wherein the imaging element can be imaged by at least one of the following imaging techniques:

x-ray,
ultrasound,
magnetic resonance imaging (MRI),
computer assisted tomography (CAT),
mammography,
fluoroscopy,
Doppler,
other roentgenological imaging methods,
visualization, and
detection of emission.

4. (Previously presented) The medical device according to claim 1, wherein the imaging element comprises a portion that is bioabsorbable.

5. (Original) The medical device according to claim 4, wherein the guide element is bioabsorbable.

6. (Previously presented) The medical device according to claim 1, wherein the imaging element comprises a first portion that is non-bioabsorbable and a second portion that is bioabsorbable.

7. (Original) The medical device according to claim 6, wherein the first portion comprises titanium.

8. (Original) The medical device according to claim 6, wherein the second portion comprises collagen.

9. (Original) The medical device according to claim 1, wherein the imaging element further comprises at least one extension.

10. (Original) The medical device according to claim 9, and further comprising a bioabsorbable element mounted to the extension.

11. (Original) The medical device according to claim 10, wherein the bioabsorbable element encapsulates at least a portion of the extension.

12. (Original) The medical device according to claim 1, wherein the imaging element defines a guide element opening through which the guide element passes.

13. (Original) The medical device according to claim 12, wherein the imaging element comprises a loop that defines the guide element opening.

14. (Original) The medical device according to claim 13, wherein the guide element is a filament.

15. (Withdrawn) The medical device according to claim 14, wherein the filament is made from suture material.

16. (Previously presented) The medical device according to claim 14, wherein the filament is a metal wire.

17. (Original) The medical device according to claim 1, and further comprising a holder mounted to a portion of the guide element exterior of the tissue mass to hold the position of the guide element relative to the tissue mass.

18. (Original) The medical device according to claim 1, and further comprising a releasable connection connecting the guide element to the imaging element to form the separable portion.

19. (Original) The medical device according to claim 18, wherein the releasable connection comprises a threaded coupling.

20. (Withdrawn) The medical device according to claim 18, wherein the releasable connection is a weldment.

21. (Withdrawn) The medical device according to claim 18, wherein the releasable connection is a severable portion of the guide element.

22. (Withdrawn) The medical device according to claim 18, wherein the releasable connection is a discontinuity in the guide element.

23. (Original) The medical device according to claim 1, and further comprising a gripping element attachable to the guide element for separating the guide element from the imaging element.

24. (Previously presented) The medical device according to claim 1, wherein the imaging element is releasable to permit the repositioning of the imaging element in the tissue mass.

25. (Withdrawn) The medical device of claim 24 wherein the imaging element comprises at least one flexible hook.

26. (Original) The medical device according to claim 1, wherein the guide element is a filament.

27. (Previously presented) The medical device according to claim 26, wherein the filament comprises a length of wire.

28. (Withdrawn) The medical device according to claim 23, wherein the filament comprises a length of suture material.

29. (Withdrawn) The medical device according to claim 1, wherein the guide element comprises a bioabsorbable material.

30. (Currently amended) A method for localizing and marking an area of interest in a tissue mass, comprising the steps of:

providing a medical device comprising an imaging element and a guide element
connected to the imaging element; and

inserting the medical device into the tissue mass so that at least part of the guide element
extends exteriorly of the tissue mass; and

after the imaging element has been deployed within the tissue mass and a delivery
apparatus used to deploy the imaging element has been removed from the tissue
mass, removing at least a portion of the guide element so that no portion of the
guide element extends exteriorly of the tissue mass.

31. (Cancelled)

32. (Previously presented) The method according to claim 31, and further comprising the step of unthreading the at least a portion of the guide element to remove the at least a portion of the guide element.

33. (Previously presented) The method according to claim 31, and further comprising the step of pulling the guide element to remove the at least a portion of the guide element.

34. (Currently amended) The method according to claim 33, [a] wherein the removing step comprises cutting the guide element.

35. (Original) The method according to claim 33, wherein the removing step comprises removing the entire guide element from the tissue mass.

36. (Original) The method according to claim 33, wherein the removing step comprises separating at least a portion of the guide element from the imaging element.

37. (Original) The method according to claim 36, wherein the removing step comprises removing the entire guide element from the tissue mass.

38. (Withdrawn) The method according to claim 33, wherein the removing step comprises separating the guide element from the imaging element at a spot weld.

39. (Original) The method according to claim 34, wherein the removing step further comprises removing a cut portion of the guide element.

40. (Original) The method according to claim 30, and further comprising the step of locating the imaging element by an imaging technique.

41. (Original) The method according to claim 40, and further comprising the step of removing the at least a portion of the guide element after the locating of the imaging element.

42. (Previously presented) The method according to claim 30, and further comprising the step of locating the area of interest in the tissue mass for surgical excision by following the guide element to the imaging element.

43. (Cancelled)

44. (Previously presented) The delivery apparatus according to claim 70, and further comprising a handle to which the cannula is mounted.

45. (Previously presented) The delivery apparatus according to claim 44, wherein the handle, cannula, stylet, and medical device are operably coupled such that they form a self-contained marking apparatus that can be handled by a user to effect operation of the delivery apparatus to expel the medical device.

46. (Previously presented) The delivery apparatus according to claim 69, wherein the separable portion comprises the entire guide element.

47. (Previously presented) The delivery apparatus according to claim 69, wherein the imaging element can be imaged by at least one of the following imaging techniques:

- x-ray,
- ultrasound,
- magnetic resonance imaging (MRI),
- computer assisted tomography (CAT),
- mammography,
- fluoroscopy,
- Doppler,
- other roentgenological imaging methods,
- visualization, and
- detection of emission.

48. (Currently amended) The delivery apparatus according to claim 69, wherein the imaging element comprises a portion that is one of bioabsorbable [or] and non-bioabsorbable.

49. (Original) The delivery apparatus according to claim 48, wherein the guide element is bioabsorbable.

50. (Original) The delivery apparatus according to claim 48, wherein the imaging element comprises a first portion that is non-bioabsorbable and a second portion that is bioabsorbable.

51. (Previously presented) The delivery apparatus according to claim 69, wherein the imaging element further comprises at least one extension.

52. (Original) The delivery apparatus according to claim 51, and further comprising a bioabsorbable element mounted to the extension.

53. (Previously presented) The delivery apparatus according to claim 69, wherein the imaging element defines a guide element opening through which the guide element passes.

54. (Original) The delivery apparatus according to claim 53, wherein the imaging element comprises a loop that defines the guide element opening.

55. (Original) The delivery apparatus according to claim 54, wherein the guide element is a filament.

56. (Previously presented) The delivery apparatus according to claim 69, and further comprising a holder mounted to a portion of the guide element exterior of the tissue mass to hold the position of the guide element relative to the tissue mass.

57. (Previously presented) The delivery apparatus according to claim 45, and further comprising a releasable connection connecting the guide element to the imaging element to form the separable portion.

58. (Original) The delivery apparatus according to claim 57, wherein the releasable connection comprises a threaded coupling.

59. (Withdrawn) The delivery apparatus according to claim 57, wherein the releasable connection is a weldment.

60. (Withdrawn) The delivery apparatus according to claim 57, wherein the releasable connection is a severable portion of the guide element.

61. (Withdrawn) The delivery apparatus according to claim 57, wherein the releasable connection is a discontinuity in the guide element.

62. (Previously presented) The delivery apparatus according to claim 69, wherein the guide element is a filament.

63. (Original) The delivery apparatus according to claim 62, wherein the filament comprises a length of wire.

64. (Withdrawn) The delivery apparatus according to claim 62, wherein the filament comprises a length of suture material.

65. (Withdrawn) The delivery apparatus according to claim 45, wherein the guide element comprises a bioabsorbable material.

66. (Previously presented) The delivery apparatus according to claim 69, and further comprising a gripping element attachable to the guide element for separating the guide element from the imaging element.

67. (Previously presented) The delivery apparatus according to claim 69, wherein the imaging element is releasable to permit the repositioning of the imaging element in the tissue mass.

68. (Withdrawn) The delivery apparatus of claim 67 wherein the imaging element comprises at least one flexible hook.

69. (Currently amended) A delivery apparatus for the percutaneous placement of a medical device at an area of interest in a tissue mass to facilitate subsequent determination of the area of interest, comprising:

- an introducer defining a lumen having a proximal end and a distal end defining an expulsion opening;

- a piston having a distal end slidably received within the lumen, and wherein when the delivery apparatus is in a ready position, the distal end of the piston is spaced inwardly from the expulsion opening to form a recess between the distal end of the piston and the expulsion opening; and

- a medical device comprising:

- an imaging element positioned in the recess for subcutaneous placement in a tissue mass to identify an area of interest in the tissue mass; and

- a guide element connected to the imaging element and having a separable portion; and

- ~~wherein the expulsion opening is positioned into the tissue mass such that~~ when the piston is advanced into the recess, at least the imaging element is expelled through the expulsion opening into the tissue mass, and wherein the imaging element and the guide element are connected, such that after ~~when~~ the expulsion opening is withdrawn from the tissue mass, (i) the imaging element while still connected to

the guide element is placed within the tissue mass at the area of interest, and at least part of the guide element extends exteriorly of the tissue mass, and (ii) ~~after placement when the separable portion is~~ adapted to be separated from the guide element, such that no part of the guide element extends exteriorly of the tissue mass.

70. (Previously presented) The delivery apparatus according to claim 69, wherein the introducer comprises a cannula defining the lumen and the piston comprises a stylet.

71. (Previously presented) The medical device according to claim 1, wherein the imaging element comprises a portion that is non-bioabsorbable.